

## Product Variants in **GRT SERIES (Three Phase)**

Product Code	Blade Description	Blade Speed	Cutting Ability	Power	Net Weight	Standard Blade	Features
GRTMINI	Ø 86 mm (3.4")	550 r.p.m.	25 mm (1")	55 W	2.65 Kg	86PHSS 5-edges HSS Steel	Carbide Counter-Blade.
GRTMINIV	Ø 86 mm (3.4")	550 r.p.m.	25 mm (1")	55 W	2.65 Kg	86PHSS 5-edges HSS Steel	Carbide Counter-Blade. Motor mounted vertically.
GRT10	Ø 100 mm (4")	550 r.p.m.	35 mm (1.4")	75 W	2.8 Kg	10EHSS 6-edges HSS Steel	
GRT10L	Ø 100 mm (4")	550 r.p.m.	35 mm (1.4")	75 W	2.8 Kg	10EHSS 6-edges HSS Steel	Left Side Version of GRT-10.
GRT12	Ø 120 mm (4.7")	400 r.p.m.	50 mm (2")	180 W	4.65 Kg	12SHSS 8-edges HSS Steel	
GRT12SX	Ø 120 mm (4.7")	400 r.p.m.	50 mm (2")	180 W	4.65 Kg	12SHSS 8-edges HSS Steel	Left Side Version of GRT-12.
GRT12M	Ø 120 mm (4.7")	400 r.p.m.	50 mm (2")	180 W	4.6 Kg	12SHSS 8-edges HSS Steel	Monster Series. Motor housing is held by a central foot, fixed behind the blade in central position. Motor comes with bronze / steel couplings.
GRT12SM	Ø 120 mm (4.7")	400 r.p.m.	50 mm (2")	180 W	4.6 Kg	12SHSS 8-edges HSS Steel	Left Side Version of GRT-12M.
GRT12DT	Ø 120 mm (4.7")	400 r.p.m.	50 mm (2")	180 W	4.59 Kg	12SHSS 8-edges HSS Steel	Double carbide counter blade, can cut on both directions. Motor comes with bronze / steel couplings.